









| Dimenzije | | Material | Oznaka na dokumentaciji |
|-----------|------------|--------------------------------------|-------------------------|
| DN | Ø x s | | |
| 30 | 32x3,0 mm | Polietilen visoke gostote (PE-HD) | PE-Plu. |
| 40 | 40x3,0 mm | | |
| 50 | 50x3,0 mm | | |
| 56 | 56x3,0 mm | | |
| 60 | 63x3,0 mm | | |
| 70 | 75x3,0 mm | | |
| 90 | 90x3,5 mm | | |
| 100 | 110x4,3 mm | | |
| 125 | 135x4,9 mm | | |
| 150 | 160x6,2 mm | | |

*Za osovode podtladne meteorne kanalizacije.
 ** Varjeni spoji.

| | |
|---|---|
| * Simboli: | |
|  | DN50 |
|  | krogelni ventili |
|  | polnilno-praznilna pipa ali blindiran krogelni ventili DN15 |
|  | balansirni ventili |
|  | večfunkcijski termostatski obtočni ventili |
|  | protipovratni ventili |
|  | OV-FE |
|  | avtomatični odzračevalni ventili |
|  | Č.K. DN125 |
|  | čistilni / revizijski kos |
|  | LSAH |
|  | LSAH 18.04 |
|  | LSAL |
|  | LSAL 18.03 |
|  | LIC |
|  | LIC 18.05 |
|  | Y 18.06 |
|  | Y 18.06 |
|  | črpalka |
|  | P 18.02 |

Stanje na dan: 08.11.2025

[illegible]